

# FP-2000



## ■ FP-2000

**Product Code: 10149**

Product Description: **FirePro Fire Extinguishing Generator FP-2000.**

Features:

- UL, KIWA, BSI, ActivFire Approved
- Carbon-Steel casing Red-coated

## ■ FP-2000T

**Product Code: 10317**

Product Description: **FirePro Fire Extinguishing Generator FP-2000T.**

Features:

- Under Process to be UL, KIWA, BSI, ActivFire Approved
- This model can be activated by a Bulb Thermal Activator.
- Carbon-Steel casing Red-coated

## ■ FP-2000S

**Product Code: 10392**

Product Description: **FirePro Fire Extinguishing Generator FP-2000S.**

Features:

- UL, KIWA, BSI, ActivFire Approved
- Stainless steel casing

## ■ FP-2000TS

**Product Code: 10623**

Product Description: **FirePro Fire Extinguishing Generator FP-2000TS.**

Features:

- Under Process to be UL, KIWA, BSI, ActivFire Approved
- This model can be activated by a Bulb Thermal Activator
- Stainless steel casing

## TECHNICAL INFORMATION

Model	FP-2000 / FP-2000S / FP-2000T / FP-2000TS
Activation mechanism	Thermal Electrical (min 1.5V DC, 0.8A in 3-4 sec)
Activator type	Heating element with 2.3 ohm resistance
Current intensity to be tested	Maximum 5 mA
Weight (gross)	15500 g (excluding bracket)
Mass of FPC compound	2000 g
Operational discharge time	10 - 15 seconds
Discharge length	3.5 m
Dimensions	300 mm x 300 mm x 185 mm
Fire class	A, B, C, F

Operating temperatures: -54°C to +54°C | Generators are provided complete with brackets